


Specifications 规格

Nominal Voltage 额定电压	12V	
Rated Capacity(20 hour rate) 20小时率额定容量	1AH	
尺寸 Dimensions ±1mm	Length 长	97mm(3.81")
	Width 宽	43.5mm(1.71")
	Height 高	53mm(2.08")
	Total Height (with terminals) 总高含端子	58mm(2.28")
Weight 重量	Approx.0.5kg (1.1lbs)	
Standard Terminal 标准端子	F1	

Electrical Specifications 电性能

容量 Capacity 77°F(25°C)	20 hour rate (50mA) 20小时率	1.0AH
	10 hour rate (100mA) 10小时率	0.93AH
	5 hour rate (170mA) 5小时率	0.85AH
	1 hour rate (600mA) 1小时率	0.60AH
Internal Resistance 内阻	Fully charged battery 充足电	120m Ω
	77°F(25°C)	
Capacity 温度 Affected by 对容量 Temperature 影响 (20 hour rate) 20小时率	104°F(40°C)	102%
	77°F(25°C)	100%
	32°F(0°C)	85%
	5°F(-15°C)	65%
自放电 Self-Discharge 77°F(25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
Charge 充电 Constant (恒压) Voltage	循环使用: 首次充电电流低于0.30A 电压:14.4-15.0V77°F(25°C) 电压:13.5-13.8V77°F(25°C) Cycle:Initial Charging Current less than0.30A Voltage14.4-15.0V77°F(25°C) Standby: Voltage13.5-13.8V77°F(25°C)	

放电特性 Discharge Characteristics(20°C, 68°F)



放电特性 Discharge Characteristics(0°C/32°F, 40°C/104°F)

